

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** AT color - Thinner

7045, 9006, 9008, 9013, 9009, 9021

### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Cleaner

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:** Sipoon AT-Tuote Oy

Lukkarinmäentie 6 04130 Sipoo - Finland Phone.: 09-274 5500 -Fax: 09 239 3600 attuote@attuote.fi www.attuote.fi

**1.4 Emergency telephone number:** Yleinen hätänumero:112 Myrkytystietokeskus, PL 790

(Tukholmankatu 17), 00029 HUS:09-471977

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) no 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) no 1272/2008.

Asp. Tox. 1: Aspiration hazard, Category 1, H304 Eye Dam. 1: Serious eye damage, Category 1, H318 Flam. Liq. 2: Flammable liquids, Category 2, H225 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

#### 2.2 Label elements:

# CLP Regulation (EC) no 1272/2008:

## Danger









# **Hazard statements:**

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Dam. 1: H318 - Causes serious eye damage Flam. Liq. 2: H225 - Highly flammable liquid and vapour Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 3: H336 - May cause drowsiness or dizziness

## **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P264: Wash thoroughly after use

P280: Wear protective gloves/protective clothing/eye protection/face protection

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

### Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

## **Substances that contribute to the classification**

Toluene; Butyl Acetate; Isobutanol

#### 2.3 Other hazards:



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

## SECTION 2: HAZARDS IDENTIFICATION (continue)

Non-applicable

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Solvent/s

#### Components:

In accordance with Annex II of Regulation (EC) nº1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification			
CAS:	108-88-3	Toluene	ATP CLP00			
	203-625-9 601-021-00-3 : 01-2119471310-51-XXXX	,	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	50 - <75 %		
CAS:	123-86-4	Butyl Acetate	ATP CLP00			
	204-658-1 607-025-00-1 : 01-2119485493-29-XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	25 - <50 %		
CAS:	70 03 1	Isobutanol	ATP CLP00			
	201-148-0 603-108-00-1 : 01-2119484609-23-XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	10 - <25 %		

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

# **SECTION 4: FIRST AID MEASURES**

# 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

## By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1 Extinguishing media:

Date of compilation: 2/24/2014 Revised: 6/17/2015 Version: 5 (Replaced 4) **Page 2/12** 



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

## SECTION 5: FIREFIGHTING MEASURES (continue)

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

# 6.2 Environmental precautions:

This product is not classified as dangerous to the environment. Keep product away from drains, surface and underground water.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

# SECTION 7: HANDLING AND STORAGE (continue)

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximun Temp.: 30 °C
B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
Toluene	IOELV (8h)	50 ppm	192 mg/m <sup>3</sup>
CAS: 108-88-3	IOELV (STEL)	100 ppm	384 mg/m <sup>3</sup>
EC: 203-625-9	Year	2014	

# **DNEL (Workers):**

		Short e	xposure	Long ex	cposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m³	384 mg/m <sup>3</sup>	192 mg/m³	192 mg/m³
Butyl Acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	960 mg/m³	960 mg/m³	480 mg/m³	480 mg/m³
Isobutanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-83-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 201-148-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m <sup>3</sup>

# **DNEL (General population):**

		Short e	xposure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m³	226 mg/m <sup>3</sup>	56,5 mg/m³	56,5 mg/m³
Butyl Acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	859,7 mg/m <sup>3</sup>	859,7 mg/m³	102,34 mg/m <sup>3</sup>	102,34 mg/m <sup>3</sup>
Isobutanol	Oral	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
CAS: 78-83-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 201-148-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	55 mg/m <sup>3</sup>

# PNEC:

Identification				
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg
Butyl Acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg

Date of compilation: 2/24/2014 Revised: 6/17/2015 Version: 5 (Replaced 4) **Page 4/12** 



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Identification				
Isobutanol	STP	10 mg/L	Fresh water	0,4 mg/L
CAS: 78-83-1	Soil	0,0699 mg/kg	Marine water	0,04 mg/L
EC: 201-148-0	Intermittent	11 mg/L	Sediment (Fresh water)	1,52 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,152 mg/kg

#### 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the CE marking in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the professional exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves	CATI	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	Replace the gloves at any sign of deterioration.

### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against liquid splash	CATII	EN 166:2001 EN 172:1994/A1:2000 EN 172:1994/A2:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

## E.- Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI	EN ISO 13688:2013	For professional use only.
	Anti-slip work shoes	CATII	EN ISO 20347:2012 EN ISO 20344:2011	None

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 100 % weight

V.O.C. density at 20 °C: 866,69 kg/m³ (866,69 g/L)



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Average carbon number: 6,3

Average molecular weight: 99,94 g/mol

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Color:

Colourless

Odor:

Characteristic

Volatility:

Boiling point at atmospheric pressure: 116 °C Vapour pressure at 20 °C: 2188 Pa

Vapour pressure at 50 °C: 9732 Pa (10 kPa)

Evaporation rate at 20 °C: 2,4

**Product description:** 

Density at 20 °C: 867 kg/m³

Relative density at 20 °C: 0,867

Dynamic viscosity at 20 °C: 0,83 cP

Kinematic viscosity at 20 °C: 0,95 cSt

Kinematic viscosity at 40 °C: <20,5 cSt

Concentration: Non-applicable \*

pH: Non-applicable \*
Vapour density at 20 °C: Non-applicable \*
Partition coefficient n-octanol/water 20 °C: Non-applicable \*
Solubility in water at 20 °C: Non-applicable \*
Solubility properties: Non-applicable \*
Decomposition temperature: Non-applicable \*
Melting point/freezing point: Non-applicable \*

Flammability:

Flash Point: 14 °C
Autoignition temperature: 421 °C
Lower flammability limit: 1 % Volume
Upper flammability limit: 7,1 % Volume

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

## 10.1 Reactivity:

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

10.2 Chemical stability:

Date of compilation: 2/24/2014 Revised: 6/17/2015 Version: 5 (Replaced 4) **Page 6/12** 



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

# SECTION 10: STABILITY AND REACTIVITY (continue)

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Not applicable	Not applicable	Avoid direct impact	Not applicable	Not applicable

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

#### A.- Ingestion:

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

## B- Inhalation:

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eves:
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Suspected of damaging the unborn child.

### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensibilizising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT)-time exposure:

Exposure in high concentrations can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of concentration.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentrations can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of concentration.
  - Skin: Repeated exposure may cause skin dryness or cracking



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

# SECTION 11: TOXICOLOGICAL INFORMATION (continue)

# H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

### Other information:

Non-applicable

# Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat
Butyl Acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Isobutanol	LD50 oral	3350 mg/kg	Rat
CAS: 78-83-1	LD50 dermal	2460 mg/kg	Rabbit
EC: 201-148-0	LC50 inhalation	24,6 mg/L (4 h)	Rat

# **SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification		Acute toxicity	Specie	Genus
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11,5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-625-9	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Algae
Butyl Acetate	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
CAS: 123-86-4	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
EC: 204-658-1		675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Isobutanol	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
CAS: 78-83-1	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-148-0	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae

# 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Toluene	BOD5	2.5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Butyl Acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	0.79	% Biodegradable	84 %
Isobutanol	BOD5	0.4 g O2/g	Concentration	100 mg/L
CAS: 78-83-1	COD	2.41 g O2/g	Period	14 days
EC: 201-148-0	BOD5/COD	0.17	% Biodegradable	90 %

# 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Toluene	BCF	13
CAS: 108-88-3	Pow Log	2,73
EC: 203-625-9	Potential	Low
Butyl Acetate	BCF	4
CAS: 123-86-4	Pow Log	1,78
EC: 204-658-1	Potential	Low
Isobutanol	BCF	3
CAS: 78-83-1	Pow Log	0,76
EC: 201-148-0	Potential	Low

Date of compilation: 2/24/2014 Revised: 6/17/2015 Version: 5 (Replaced 4) **Page 8/12** 



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

# SECTION 12: ECOLOGICAL INFORMATION (continue)

### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Toluene	Koc	178	Henry	6,728E+2 Pa·m³/mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	27930 N/m (25 °C)	Moist soil	Yes
Butyl Acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	24780 N/m (25 °C)	Moist soil	Non-applicable
Isobutanol	Koc	Non-applicable	Henry	Non-applicable
CAS: 78-83-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 201-148-0	Surface tension	23780 N/m (25 °C)	Moist soil	Non-applicable

### 12.5 Results of PBT and vPvB assessment:

Non-applicable

#### 12.6 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 29*	Detergents containing dangerous substances	Dangerous

### Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP10 Toxic for reproduction

# Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

## Regulations related to waste management:

In accordance with Annex II of Regulation (EC)  $n^{o}1907/2006$  (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# **SECTION 14: TRANSPORT INFORMATION**

# Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:

- CONTINUED ON NEXT PAGE 
Date of compilation: 2/24/2014 Revised: 6/17/2015 Version: 5 (Replaced 4) Page 9/12

at

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

## SECTION 14: TRANSPORT INFORMATION (continue)



**14.1 UN number:** UN1993

**14.2 UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Toluene)

**14.3** Transport hazard class(es): 3
Labels: 3

14.4 Packing group: II

14.5 Dangerous for the environment:

14.6 Special precautions for user

Special regulations: 274, 601, 640D

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according to Non-applicable

Annex II of MARPOL 73/78 and the IBC Code:

#### Transport of dangerous goods by sea:

With regard to IMDG 37-14:

**14.1 UN number:** UN1993

**14.2 UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Toluene)

 14.3
 Transport hazard class(es):
 3

 Labels:
 3

 14.4
 Packing group:
 II

14.5 Dangerous for the environment:

14.6 Special precautions for user

Special regulations: 274, 944

EmS Codes: F-E, S-E

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according to Non-applicable
Annex II of MARPOL 73/78

and the IBC Code:

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:



**14.1 UN number:** UN1993

**14.2 UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Toluene)

14.3 Transport hazard class(es): 3
Labels: 3

14.4 Packing group: II
14.5 Dangerous for the No

environment:

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Non-applicable

Annex II of MARPOL 73/78

and the IBC Code:

#### **SECTION 15: REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Non-applicable

Date of compilation: 2/24/2014 Revised: 6/17/2015 Version: 5 (Replaced 4) **Page 10/12** 



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

## SECTION 15: REGULATORY INFORMATION (continue)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Regulation (EC) nº648/2004 on detergents:

In accordance with this regulation the product complies with the following:

#### Contents labelled:

Component	Concentration interval
Aromatic hydrocarbons	% (w/w) >= 30

#### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

- Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products
- Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents
- Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII
- Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)

## 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

# **SECTION 16: OTHER INFORMATION**

## Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EU) No 453/2010, Regulation (EC) No 2015/830)

### Modifications related to the previous security card which concerns the ways of managing risks. :

Directive 67/548/EC and Directive 1999/45/EC:

- · S Phrases
- CLP Regulation (EC) no 1272/2008:
  - · Precautionary statements

## Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation
- H336: May cause drowsiness or dizziness
- H373: May cause damage to organs through prolonged or repeated exposure
- H361d: Suspected of damaging the unborn child.
- H318: Causes serious eye damage
- H304: May be fatal if swallowed and enters airways
- H225: Highly flammable liquid and vapour

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) nº 1272/2008:



According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# AT color - Thinner 7045, 9006, 9008, 9013, 9009, 9021

## SECTION 16: OTHER INFORMATION (continue)

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Dam. 1: H318 - Causes serious eye damage Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness

#### Classification procedure:

Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Eye Dam. 1: Calculation method Asp. Tox. 1: Calculation method

Flam. Liq. 2: Calculation method (2.6.4.3)

### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### **Principal bibliographical sources:**

http://esis.jrc.ec.europa.eu http://echa.europa.eu http://eur-lex.europa.eu

## **Abbreviations and acronyms:**

- ADR: European agreement concerning the international carriage of dangerous goods by road
- -IMDG: International maritime dangerous goods code
- -IATA: International Air Transport Association
- -ICAO: International Civil Aviation Organisation
- -COD: Chemical Oxygen Demand
- -BOD5: 5-day biochemical oxygen demand
- -BCF: Bioconcentration factor
- -LD50: Lethal Dose 50
- -CL50: Lethal Concentration 50
- -EC50: Effective concentration 50
- -Log-POW: Octanol-water partition coefficient
- -Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET 
Date of compilation: 2/24/2014 Revised: 6/17/2015 Version: 5 (Replaced 4) Page 12/12